



**CrystalLine Self-locking roller/  
Self-locking roller Softlift/Electric**


The new reflecta CrystalLine self-locking roller and electric projection screens are extremely good value for money. The well-engineered self-locking roller and electric mechanism with remote control (only with CrystalLine electric) allows for an easy and silent extending and retracting of the projection screen. The high-grade screen fabric delivers brilliant images with any type of projection. The CrystalLine electric projection screens include a remote control.

**Product details:**

- Mounted to wall or ceiling.
- Simple installation and easy handling.
- Large viewing angle.
- Suitable for all common front projection types.
- High-quality screen BetaLux with 1.0 gain.
- Light-proof rear with black coating.
- Black border.
- Remote control included (only with electric variant).



Radio remote control (only for electric variant)



Softlift-function (only with CrystalLine self-locking roller Softlift)

**CrystalLine Self-locking roller/Self-locking roller Softlift/Electric Technical data (all dimensions in cm)**

Art.No.	Type	Fabric	Format	A	B	C	D	R1	R2	R3	E	F	G	J	Weight
87660	CrystalLine self-locking roller	BetaLux	1:1	160	160	156	156	2	2	2	175	6,8	6,8	165	6 kg
87661	CrystalLine self-locking roller	BetaLux	1:1	180	180	176	176	2	2	2	195	6,8	6,8	185	7 kg
87662	CrystalLine self-locking roller	BetaLux	1:1	200	200	196	196	2	2	2	215	6,8	6,8	205	9 kg
87663	CrystalLine self-locking roller	BetaLux	1:1	240	240	236	236	2	2	2	255	6,8	6,8	245	13 kg
87664	CrystalLine self-locking roller	BetaLux	1:1	300	300	292	292	4	4	4	315	8,9	8,9	305	16 kg
87685	CrystalLine self-locking roller	BetaLux	4:3	160	129	156	117	2	10	2	175	6,8	6,8	165	6 kg
87680	CrystalLine self-locking roller	BetaLux	4:3	180	144	176	132	2	10	2	195	6,8	6,8	185	7 kg
87681	CrystalLine self-locking roller	BetaLux	4:3	200	159	196	147	2	10	2	215	6,8	6,8	205	9 kg
87682	CrystalLine self-locking roller	BetaLux	4:3	220	174	216	162	2	10	2	235	6,8	6,8	225	10 kg
87683	CrystalLine self-locking roller	BetaLux	4:3	240	189	236	177	2	10	2	255	6,8	6,8	245	11 kg
87684	CrystalLine self-locking roller	BetaLux	4:3	300	233	292	219	4	10	4	315	8,9	8,9	305	16 kg
87700	CrystalLine self-locking roller	BetaLux	16:9	160	130	156	88	2	40	2	175	6,8	6,8	165	6 kg
87701	CrystalLine self-locking roller	BetaLux	16:9	180	141	176	99	2	40	2	195	6,8	6,8	185	7 kg
87702	CrystalLine self-locking roller	BetaLux	16:9	200	152	196	110	2	40	2	215	6,8	6,8	205	8 kg
87703	CrystalLine self-locking roller	BetaLux	16:9	240	175	236	133	2	40	2	255	6,8	6,8	245	10 kg
87704	CrystalLine self-locking roller	BetaLux	16:9	300	208	292	164	4	40	4	315	8,9	8,9	305	16 kg
87720	CrystalLine self-locking roller Softlift	BetaLux	1:1	160	160	156	156	2	2	2	175	6,8	6,8	165	6 kg
87721	CrystalLine self-locking roller Softlift	BetaLux	1:1	180	180	176	176	2	2	2	195	6,8	6,8	185	7 kg
87722	CrystalLine self-locking roller Softlift	BetaLux	1:1	200	200	196	196	2	2	2	215	6,8	6,8	205	9 kg
87723	CrystalLine self-locking roller Softlift	BetaLux	1:1	240	240	236	236	2	2	2	255	6,8	6,8	245	13 kg
87730	CrystalLine self-locking roller Softlift	BetaLux	4:3	180	144	176	132	2	10	2	195	6,8	6,8	185	7 kg
87731	CrystalLine self-locking roller Softlift	BetaLux	4:3	200	159	196	147	2	10	2	215	6,8	6,8	205	9 kg
87732	CrystalLine self-locking roller Softlift	BetaLux	4:3	220	174	216	162	2	10	2	235	6,8	6,8	225	10 kg
87670	CrystalLine Electric	BetaLux	1:1	160	160	156	156	2	2	2	187	8,9	8,9	165	9 kg
87671	CrystalLine Electric	BetaLux	1:1	180	180	176	176	2	2	2	207	8,9	8,9	185	11 kg
87672	CrystalLine Electric	BetaLux	1:1	200	200	196	196	2	2	2	227	8,9	8,9	205	13 kg
87673	CrystalLine Electric	BetaLux	1:1	240	240	236	236	2	2	2	267	8,9	8,9	245	15 kg
87674	CrystalLine Electric	BetaLux	1:1	300	300	292	292	4	4	4	327	8,9	8,9	305	24 kg
87690	CrystalLine Electric	BetaLux	4:3	160	129	156	117	2	10	2	187	8,9	8,9	165	9 kg
87691	CrystalLine Electric	BetaLux	4:3	180	144	176	132	2	10	2	207	8,9	8,9	185	10 kg
87692	CrystalLine Electric	BetaLux	4:3	200	159	196	147	2	10	2	227	8,9	8,9	205	13 kg
87693	CrystalLine Electric	BetaLux	4:3	240	189	236	177	2	10	2	267	8,9	8,9	245	15 kg
87694	CrystalLine Electric	BetaLux	4:3	300	233	292	219	4	10	4	327	8,9	8,9	305	24 kg
87710	CrystalLine Electric	BetaLux	16:9	160	130	156	88	2	40	2	187	8,9	8,9	165	9 kg
87711	CrystalLine Electric	BetaLux	16:9	180	141	176	99	2	40	2	207	8,9	8,9	185	10 kg
87712	CrystalLine Electric	BetaLux	16:9	200	152	196	110	2	40	2	227	8,9	8,9	205	13 kg
87713	CrystalLine Electric	BetaLux	16:9	240	175	236	133	2	40	2	267	8,9	8,9	245	15 kg
87714	CrystalLine Electric	BetaLux	16:9	300	208	292	164	4	40	4	327	8,9	8,9	305	24 kg

